



技术要求:

1. 插入损耗: $\leq 0.2\text{db}$
2. 工作温度: $-40\text{ (}^\circ\text{C)} \sim +85\text{ (}^\circ\text{C)}$
3. 吊重实验: $\geq 70\text{N}$
4. 插拔次数: $\geq 500\text{次}$

序号	图纸编号	名称	数量	材料
1	OYH-JS-S-SC-019	销钉	1	SUS304
2	OYH-JS-S-SC-021	簧片	1	铍青铜
3	OYH-JS-S-SC-020	防尘盖	1	PC
4	OYH-JS-S-SC-022	底盖	1	PC
5	OYH-JS-S-SC-017	挂钩	2	PBT
6	OYH-JS-S-SC-018	陶瓷套管	1	陶瓷
7	OYH-JS-S-LC-052	单联弹片	1	SUS304
8	OYH-JS-S-SC-031	斜门壳体有耳	1	PC
9	OYH-JS-S-SC-004	T型方口防尘帽	1	PC

产品名称: SC推入式有耳适配器		图号: OYH-JS-ZP-009
绘制: 陈旭斌	审核:	批准:
日期: 2018.4.28	日期:	日期:
比例: 2:1	单位: mm	版本: A/2
浙江欧亚华通讯设备有限公司 ZHEJIANG OYARWA COMMUNICATION EQUIPMENT CO.,LTD.		